



# DAIKIN ONE LITE CONNECTED THERMOSTAT

## Description

The Daikin *ONE* lite connected thermostat is a perfect solution for Daikin single and multi-zone products when a wall-mounted smart thermostat is needed. The Daikin *ONE* lite connected thermostat is compatible with most Daikin single and multi-zone systems and can be linked via Wi-Fi to the *SkyportHome* app for control.

## Standard Features

- Compact, non-intrusive design suitable for most interior environments
- Multifunction push buttons labeled for mode, fan, set-point up, set-point down
- Wi-Fi-enabled connected thermostat that works with *SkyportHome* app (iOS and Android)
- Voice control by Amazon Alexa and Google Assistant
- Programmable schedule
- Built-in temperature and humidity sensors
- Indoor unit Control: Mode (Auto/Heat/Cool/Emergency Heat), Setpoint (Dual/Single), Fan Speed, Fan On/Auto (with minimum run time)
- LED Mode indicator for heating and cooling
- Dehumidification function (setup with *SkyportCare* app)
- Error and maintenance notifications
- Control and comfort functions: Away mode and geo-fencing
- Over-the-air software update capable (requires Wi-Fi connection)
- Compatible with *SkyportCare*
- Setup is possible within the *SkyportCare* app via the *Quality Install* tool.

## Technical Specifications

- Backlit, 3.5 inch MVA TFT LCD display
- Bi-directional communications protocol for controlling HVAC system
- Multi-language support: English, Spanish, French (*SkyportCare* app only)
- 1 Auxiliary Heat output (dry contact), configurable as a primary or secondary heat source for heat pump systems only.
- Includes Translation adaptor for S21 systems. (Note this control is not for use with P1P2 systems).
- FCC Certified/UL Listed
- An optional trim plate (PSPAC-WPM-L) is available.

## Product Dimensions

- 3.3"W x 3.3"H x 1.04"D

## Product Number

- DTST-LTE-LA-A



R32



	Type	Compatible Family (Models starting with)
Ductless Mini & Multi-Split Systems	R-410A S21 Indoor Units <sup>1</sup>	CDXS, CTXS <sup>2</sup> , FDXS, FTK <sup>2</sup> , FTXB <sup>2</sup> , FTXF <sup>2</sup> , FTXG <sup>2</sup> , FTX09_12N <sup>2</sup> , FTX15_18_24N <sup>3</sup> , FTXR, FTXS, FVXS <sup>3</sup>
	R-32 S21 Indoor Units <sup>1</sup>	FTXC, FTXV(09/12/15/18/24) <sup>2</sup> , FTXV(30/36) <sup>4</sup> , CTXV <sup>2</sup> , FTKF_B <sup>2</sup> , FVXV <sup>4</sup> , FTXF_B <sup>2</sup> , FTXM <sup>4</sup>

<sup>1</sup> Must install provided communication adaptor that comes with DTST-LTE-LA-A

<sup>2</sup> Must purchase S21 adaptor KRP067A41E

<sup>3</sup> Must purchase S21 adaptor KRP980B2E

<sup>4</sup> The Sarara drying function of the *QUATERNITY* units is not supported with Daikin *ONE* lite connected thermostat, but the dehumidification function of the Daikin *ONE* lite can be used with the *QUATERNITY* indoor units



\* Complete warranty available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year Limited<sup>1</sup> Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage may depend on the state in which you reside. Some states and provinces do not allow warranty coverage to be conditioned on registration. For a list of states and provinces that do not allow warranty coverage to be conditioned on registration, please visit [www.daikincomfort.com/warranty-information](http://www.daikincomfort.com/warranty-information) or, to request a paper copy of this information, please call us at 1-855-502-3903. Other limitations and exclusions apply, refer to complete warranty details for full list of limitations and exclusions.

<sup>1</sup> 12-Year Limited Warranty is available for owner-occupied residences only. For multi-family and/or commercial applications, the warranty period is 5-years.

